

## Wetting and Dispersing Agent

### GENERAL INFORMATION

Disponer 9250 is a copolymer with acidic groups, it is particularly effective in the wetting of inorganic pigment or filler therefore reduces viscosity of coating system.

### PHYSICAL PROPERTIES

Composition	solution of a copolymer with acidic groups
Appearance	yellow liquid
Non-volatile content	48.5 - 51.5%
Solvent	Solvent naphtha / Propylene glycol methyl ether acetate
Specific gravity	1.01 - 1.05
Refractive index	1.449 - 1.454 (25°C)

### APPLICATIONS

- acrylic PU
- acrylic / melamine
- car refinish
- coil coatings

### KEY PROPERTIES

- Disponer 9250 is an excellent wetting and dispersing agent for the stabilization of inorganic pigments in coating system.
- Disponer 9250 does not cause yellowing of paint film.

### INCORPORATION

- Incorporated before grinding and dispersed with pigment to achieve optimum effect.
- Please dilute with solvent before use.
- Please check the optimum dosage and test compatibility before use.

### LEVELS OF USE

- Inorganic pigment : 2 - 5% based on pigment.
- Organic pigment : 2 - 5% based on pigment.

### HANDLING AND SAFETY

- As it contains solvents, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check to MSDS.

### STORAGE RECOMMENDATIONS

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 10°C to 40°C.
- Below 18°C , appearance may be cloudy or separation, please heat (water bath) to clear then stir uniform.

### PACKAGING

Net Weight: 200 kg / 25 kg

*NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.*

*© Copyright 2006, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.*

*® Trademark of Elementis Specialties, Inc.*

[www.elementis-specialties-asia.com](http://www.elementis-specialties-asia.com)

B01 Jan-10

## **SHELF LIFE**

Disponer 9250 has a shelf life of 12 months from date of manufacture.

## **QUALITY ASSURANCE**

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

---

### **Elementis Specialties, Asia**

#### **Head Office**

99, Liyang Road, Songjiang  
Industrial Zone, Shanghai,  
China 201613  
Tel.: +86 21 57740348  
Fax.: +86 21 57743563

#### **Taiwan**

92, Kuang-Fu North Road, Hsinchu  
Industrial Park, Hukou,  
Hsinchu, Taiwan  
Tel.: +886 3 5984035  
Fax.: +886 3 5983301

#### **Malaysia**

Lot PT 55, 64 & 65,  
Jalan Hulu Tinggi 26/6, Seksyen 26,  
40400 Shah Alam Selangor Darul  
Ehsan, Malaysia  
Tel.: +603 5191 9979  
Fax.: +603 5191 6811

#### **Japan**

15-14 Minaminisemba 1-Chome  
Chou-Ku, Osaka  
542-0081 Japan  
Tel.: +81 6 6267 6210  
Fax.: +81 6 6267 6213