

Leveling Agent

GENERAL INFORMATION

Levaslip 876 is a good compatibility polysiloxane surface additive to provide good substrate wetting, anti-cratering performance, slip and excellent leveling for wood coatings, and general industrial coatings.

PHYSICAL PROPERTIES

Composition	modified polysiloxane
Appearance	colorless to slight yellow clear liquid
Non-volatile content	12.0 - 14.0%
Solvent	xylene / ethylene glycol phenyl ether
Specific gravity	ca. 0.93
Refractive index	1.49 - 1.50 (25°C)

APPLICATIONS

solvent-based coatings

KEY PROPERTIES

- To provide good substrate wetting and good anti-crater.
- To reduce coefficient of friction, improves scratch resistance, mar resistance and anti-blocking properties.
- If need to re-coat, please test recoatability.

INCORPORATION

It is recommended to carry out serial test of Levaslip 876 at various level to obtain optimum dosage.

LEVELS OF USE

0.2 - 0.5% based on total formulation.

HANDLING AND SAFETY

- As it contains solvents, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

STORAGE RECOMMENDATIONS

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C to 35°C, above 35°C may due to slightly haze, but not affect performance.

PACKAGING

Net Weight: 180 kg / 25 kg

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2006, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Trademark of Elementis Specialties, Inc.

www.elementis-specialties-asia.com

B01 Dec-09

SHELF LIFE

Levaslip 876 has a shelf life of 18 months from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

Elementis Specialties, Asia

Head Office

99, Liyang Road, Songjiang
Industrial Zone, Shanghai,
China 201613
Tel.: +86 21 57740348
Fax.: +86 21 57743563

Taiwan

92, Kuang-Fu North Road, Hsinchu
Industrial Park, Hukou,
Hsinchu, Taiwan
Tel.: +886 3 5984035
Fax.: +886 3 5983301

Malaysia

Lot PT 55, 64 & 65,
Jalan Hulu Tinggi 26/6, Seksyen 26,
40400 Shah Alam Selangor Darul
Ehsan, Malaysia
Tel.: +603 5191 9979
Fax.: +603 5191 6811

Japan

15-14 Minamisemba 1-Chome
Chou-Ku, Osaka
542-0081 Japan
Tel.: +81 6 6267 6210
Fax.: +81 6 6267 6213