

Leveling Agent

GENERAL INFORMATION

Levelol 495 is a silicone-free flow and leveling agent used in solvent based coatings.

PHYSICAL PROPERTIES

Composition	acrylic copolymer
Appearance	colorless to slight yellow clear liquid
Non-volatile content	48 - 52%
Solvent	xylene
Specific gravity	ca. 0.95
Refractive index	1.478 - 1.488 (25°C)

APPLICATIONS

solvent-based coatings

KEY PROPERTIES

- To improve leveling flowing and foam-releasing.
- No side-effect the intercoat.
- It is light stable, hydrolysis resistant and does not migrate from paint film.
- Due to its nonvolatility, it can plasticize the paint films of N/C and A/C lacquer.

INCORPORATION

Please test compatibility and optimum dosage before practical use.

LEVELS OF USE

0.2 - 1.0% based on total formulation.

HANDLING AND SAFETY

- As it contains solvents, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check to MSDS.

STORAGE RECOMMENDATIONS

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C to 40°C.

PACKAGING

Net Weight: 25 kg

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2006, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Trademark of Elementis Specialties, Inc.

www.elementis-specialties-asia.com

B01 Jan-10

SHELF LIFE

Levelol 495 has a shelf life of 18 months from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

[Elementis Specialties, Asia](#)

Head Office

99, Lianyang Road, Songjiang
Industrial Zone, Shanghai,
China 201613
Tel.: +86 21 57740348
Fax.: +86 21 57743563

Taiwan

92, Kuang-Fu North Road, Hsinchu
Industrial Park, Hukou,
Hsinchu, Taiwan
Tel.: +886 3 5984035
Fax.: +886 3 5983301

Malaysia

Lot PT 55, 64 & 65,
Jalan Hulu Tinggi 26/6, Seksyen 26,
40400 Shah Alam Selangor Darul
Ehsan, Malaysia
Tel.: +603 5191 9979
Fax.: +603 5191 6811

Japan

15-14 Minaminisemba 1-Chome
Chou-Ku, Osaka
542-0081 Japan
Tel.: +81 6 6267 6210
Fax.: +81 6 6267 6213